

---

**Description of Service**

Electric service furnished under this tariff will be alternating current, 60 hertz, single or three-phase, at one of the nominal standard voltages given as follows.

**Secondary Voltages**

## a. Standard Voltages:

Single-phase, 120 volt, two-wire, grounded  
Single-phase, 120/240 volt, three-wire, grounded

Three-phase, 208Y/120 volt, four-wire grounded, wye  
Three-phase, 480Y/277 volt, four-wire, grounded, wye

## b. Alternate Voltages:

Under certain conditions and at the option of Company the following voltages may be provided: single-phase, 120/208 volt, three-wire, grounded; three-phase, 120/240 volt, four-wire, grounded, delta (overhead only); and, other voltages.

## c. Secondary delivery limitations:

Company, at its option, may limit the maximum or minimum load served at any of the above secondary voltages through a single point of delivery to a size commensurate with the capacities of transformers of that voltage designated as a Company Standard.

**Primary Voltages**

## a. Standard Primary Voltages are 7,200/12,470, 12,000/20,800, and 19,900/34,500 volt four-wire grounded. Three phase or single phase metering points can be provided.

## b. There are other primary voltages in use by Company, including 2,400/4,160 volt, wye. All primary voltages are limited to the voltages on the Company's local distribution lines and are subject to future conversion to the standard voltages listed in "a" above.

## c. Primary or greater voltage delivery is subject to local availability of those voltages, any special conditions and restrictions that Company may determine to be necessary, and the Consumer signing a written contract.